



www.stutrailers.com

HYDRAULIC STEERING LOW LOADER TRAILER

SEMI-TRAILERS LOW LOADER TRAILERS


Lowbed · Low Loader · Flatbed · Tipper · Container · Car Transporter
STU Trailers® Company Ltd. · Karatay / Konya / Türkiye · Exporting to 60 countries

+90 541 336 63 77
sales@stutrailer.com
www.stutrailer.com

2 PENDULAR AXLE DOUBLE EXTENDABLE LOW LOADER



TECHNICAL DRAWING



SPECIFICATIONS

GENERAL DETAILS

Speed : 80KM/H

Total Gross Weight : 54.800 KGS

Kingpin Weight : 24.000 KGS

Total Axle Weight : 30.800 KGS

Empty Weight of Lowbed : 16.500 KGS - +%3 Legal Loading Cap. : 38.300 KGS - +%3

GOOSENECK

King pin load technical : 24.000 kg

For Truck : Suitable with 6x2 - 6x4 --- Short 8x4

CHASSIS : Completely S355JR + S700MC strength steel welded with robotic arc welding machine high tension production. On platform every 50cm width extension bars

AXLES : 4 x 7.700 Kgs Capacity - GIGANT Brand Axles, All Axles are automatic hydraulic steering 4 x High Capacity hydraulic suspension cylinders, 4 x 24/30 emergency brake chambers, Drum Brake System, 4 x automatic slack adjuster, Hydraulic Steering System, Emergency Brake, Load Arrangement Ventil,


BRAKE : Wabco 4s-3m EBS Brake System, Drum brake System, Emergency Brake System, Loading Settings valve,

REMOTE CONTROL FUNCTIONS : Remote control for hydraulic steering, Turns to axles right and left, Zero Position for axles

TYRES : 8 +1 Tyres 265/70 R19,5 (J Type) Fulda or Pirelli or Starmaxx Brand 8 +1Pcs 19,5" Rims

ACCESSORIES : • 8 x Red+White Expanding to Sides Heavy Loading Reflectors: Front and Back side red+White • At back side of plate there will be 1 electrical sockets and lamp brackets to use turning lamps • Detachable Container Locks for 1x40 feet and 2x20 feet containers, • 18 Units x 2500 mm (2 Pieces in 1 Unit interlocking) Side bars and holes / Fixing Bars • 4 Pieces tables with 50x100mm Bar Hole inside of extension arms • 16 Tonnes chain lashing rings sides, 2 pcs of warning turning lamps, Fire box, Wheel chock, Load lashing rings • Front Ramp for loading with wheel • 1x Spare Receiver + 1 x Spare Remote Control • All woods will be beech tree (Tropical) • All hydraulic connections will be with Faster Brand easy connection

DETAIL PICTURES



sales@stutrailer.com

www.stutrailer.com

2 AXLE DOUBLE EXTENDABLE LOW LOADER



CLICK for
VIDEO




HYDRAULIC STEERING

DETAIL PICTURES



TECHNICAL DRAWING



SPECIFICATIONS

GENERAL DETAILS

Legal loading capacity : 36.000 Kgs (With Trailer Weight)

King Pin Loading Capacity : 24.000 Kgs

Total Length in open position : 12.700 mm (6.800mm + 5.500mm) + 2800mm Axles area

Width : 2.550 mm + (25 cm Right and Left Flags Expanders)

Platform Length : 6.800 mm

Hydraulic Gooseneck Length : 3.100 mm Dead Weight(approximately) :13.000 Kg (+ %3)

GOOSENECK

King pin load technical : 24.000 kg

For Truck : Suitable with 6x2 - 6x4 --- Short 8x4

CHASSIS : Completely S355JR + S700MC strength steel welded with robotic arc welding machine high tension production. On platform every 50cm width extension bars

AXLES : Trax Brand Axles 2 x 9 Tonnes Axles, All Axles are automatic hydraulic steering High Capacity air suspension balloons 2 x 24 brake chamber, 2 x 24/30 emergency brake chambers 4 x automatic slack adjuster, Rexroth Hydraulic Steering System,

BRAKE : Drum brake System, SURGE Brake System Loading Settings valve, Wabco Double Line EBS

REMOTE CONTROL FUNCTIONS : Remote control hydraulic steering, Set up gooseneck lifting, Set up platform lifting, Turns to axles right and left

TYRES : 8 Pcs vies 245/65 R17,5 (J) 8 Pcs 17,5" Rims

ACCESSORIES : At the front of lowbed, back side of red+White reflector "Convoi Exceptionnel " plate will be at back side at lowbed plate At back side of plate there will be 2 electrical sockets and lamp brackets to use turning lamps Detachable Container Locks for 40 feet and 20 feet containers 2 x Long vehicle warning plates with LED lamps 1 pcs of 3,5 inch king pin, 16 Tonnes chain lashing rings sides 4 pcs of warning turning lamps

ELECTRICAL SYSTEM : Dasteri brand electrical system suitable for EU regulation 24 V, ABS jack, 2 pcs 7 function stop lamp, 2 pcs plate lamp, Side lamps

sales@stutrailer.com

www.stutrailer.com




2 AXLE EXTENDABLE LOW LOADER



HYDRAULIC STEERING

TECHNICAL DRAWING



SPECIFICATIONS

GENERAL DETAILS

Legal loading capacity : 36.000 Kgs (With Trailer Weight)

King Pin Loading Capacity : 24.000 Kgs

Total Length in open position : 12.700 mm (6.800mm) + 2800mm Axles area

Width : 2.550 mm + (25 cm Right and Left Flags Expanders)

Platform Length : 6.800 mm

Hydraulic Gooseneck Length : 3.100 mm Dead Weight(approximately) : 13.000 Kg (+ %3)

GOOSENECK

King pin load technical : 24.000 kg

For Truck : Suitable with 6x2 - 6x4--- Short 8x4

CHASSIS : Chassis: Completely S355JR + S700MC strength steel welded with robotic arc welding machine high tension production. On platform every 50cm width extension bars

AXLES : Trax Brand Axles 2x 9 Tonnes Axles, All Axles are automatic hydraulic steering High Capacity air suspension balloons 2 x 24 brake chamber, 2 x 24/30 emergency brake chambers 4 x automatic slack adjuster, Rexroth Hydraulic Steering System,

BRAKE : Drum brake System, Emergency Brake System Loading Settings valve, Wabco Double Line EBS


REMOTE CONTROL FUNCTIONS : Remote control hydraulic steering, Set up gooseneck lifting, Set up platform lifting, Turns to axles right and left

TYRES : 8 Pcs Tyres 245/65 R17,5 (J) 8 Pcs 17,5" Rims

ACCESSORIES : At the front of lowbed, back side of red+White reflector "Convoi Exceptionnel" plate will be at back side at lowbed plate At back side of plate there will be 2 electrical sockets and lamp brackets to use turning lamps Detachable Container Locks for 40 feet and 20 feet containers 2 x Long vehicle warning plates with LED lamps 1 pcs of 3,5 inch king pin, 16 Tonnes chain lashing rings sides 4 pcs of warning turning lamps

ELECTRICAL SYSTEM : Dasteri brand electrical system suitable for EU regulation 24 V, ABS jack, 2 pcs 7 function stop lamp, 2 pcs plate lamp, Side lamps

DETAIL PICTURES




sales@stutrailer.com

www.stutrailer.com

3 AXLE TRIPLE EXTENSIONS LOW LOADER



TECHNICAL DRAWING



SPECIFICATIONS

GENERAL DETAILS

Speed : 80 KM/H

Total Gross Weight : 60.000 KGS

Kingpin Weight : 24.000 KGS

Total Axle Weight : 33.000 KGS

Empty Weight of Lowbed : 15.000 KGS Legal Loading Cap. :45.000 KGS

Gooseneck Length : +4,640 mm

Gooseneck Turning Distance : +2.400 mm

Fifth Wheel Height : +1.480 mm Air Suspension > +55 /-125 mm STRONG Total Width >+ 2.550 mm

GOOSENECK

King pin load technical : 24.000 kg

LOADING PLATFORM

Chassis : Completely S355JR strength steel welded with robotic arc welding machine high tension production, extension parts will be made with MC700 and S960QL steel grade

Loading platform length : + 5600mm +%3 Extended total length >+ 22.740 mm Loading platform manual extended width :+Right:250mm / Left: 250mm + 150mm bumper corner to optimise rear swing

AXLES : GIGANT Drum Brand Axles 3 x 12 Tonnes Hydraulic Steering Axles Lifting / Landing Valves with Air suspension 6 x High Capacity air suspension balloons 2 x 24 brake chamber, 4 x 24/30 emergency brake chambers 6 x automatic slack adjuster, Drum Brake System

BRAKE : Drum brake system, Emergency Brake System

Wabco Double Line EB


REMOTE CONTROL FUNCTIONS : Remote Wireless control hydraulic steering, Set up platform lifting, Turns to axles right and left

TYRES : 12 Pcs Tyres 235/75 R17.5 (J) twin tyres Load Index 143J 6 Pcs 17,5" Rims

ACCESSORIES : 4 x Red+White Expanding to Sides Heavy Loading Reflectors: Front and Back side 2 x Long vehicle warning plates with LED lamps 2 x Led Working Lamps on right and left side 2 x Led Working Lamps on back side 2 pcs of warning turning lamps at rear, Fire box, Wheel chock,

Galvanised load supporters : And lashing rings (16 Tons Capacity) Also placed equally with 800mm between each one on platform and gooseneck Nails at the rear side of lowbed for Alu ramps , 6 x Container Twist Locks


DETAIL PICTURES



3 AXLE DOUBLE EXTENDABLE LOW LOADER



TECHNICAL DRAWING



SPECIFICATIONS

GENERAL DETAILS

Speed : 70KM/H

Total Gross Weight : 54.000 KGS

Kingpin Weight : 18.000 KGS

Total Axle Weight : 36.000 KGS

Empty Weight of Lowbed : 12.500 KGS Legal Loading Cap. : 41.500 KGS Gooseneck Length : 3,940 mm

Gooseneck Turning Distance : +2.350 mm

Fifth Wheel Height : +1.400 mm Total Width >+ 2.550 mm

GOOSENECK

King pin load technical : 18.000 kg

For Truck : 6x2

LOADING PLATFORM

Chassis : Completely S355JR and MC700 Level Steel strength steel welded with robotic arc welding machine high tension production

Loading platform length : + 7.100mm Extended total length > + 17.000 mm Loading platform manual extended width :+Right:250mm / Left 250mm + 150 mm bumper corner to optimise rear swing

AXLES : 3 x 12 Tonnes Hydraulic Steering Trax Brand Axles, Lifting / Landing Valves with Air Suspension 6 x High Capacity air suspension pillows Emergency Brake System, Load Arranging valve

BRAKE : Drum brake System, Emergency Brake System | Wabco Brake System, BS-E SYSTEM (Without connection cable with truck)

REMOTE CONTROL FUNCTIONS : Remote control pyrene steering, Set up gooseneck lifting, Set up platform lifting, Turns to axles right and left

TYRES : 6 Pcs Tyres 205/65/17.5 (J) twin tyres Load Index129/127 6Pcs 17,5" Rims

ACCESSORIES : 4 x Red+White Expanding to Sides Heavy Loading Reflectors: Front and Back side red+White 2 X Long vehicle warning plates with LED lamps 2 pcs of warning turning lamps AT REAR, Fire box, Wheel chock, Galvanised sticks with dimension 50x100x1000mm, And lashing rings (5 Tons) Also placed equally with 1000 mm between Nail on rear for ALuminium Ramps 12 pieces load fixing galvanised holders with 10 and 20 angle

DETAIL PICTURES




sales@stutrailer.com

www.stutrailer.com

3 AXLE LOW LOADER



TECHNICAL DRAWING



SPECIFICATIONS

CHASSIS : Completely S700MC + S690QL strength steel welded with robotic arc welding machine high tension production

King pin load technical : 24.000 kg For Truck > 4x2 - 6x2 - 6x4

AXLES : 3 x 12 Tonnes Trax Brand Axles, All Axles are automatic hydraulic steering High Capacity air suspension balloons, 2 x 24 brake chamber, 4 x 24/30 emergency brake chambers 4 x automatic slack adjuster, Hydraulic Steering System manually and with remote control system

BRAKE : Drum brake System, Emergency Brake System, Loading Settings valve, Wabco 4S-3M EBS

REMOTE CONTROL FUNCTIONS : Remote control for hydraulic steering and set up gooseneck lifting, Set up platform lifting, Turns to axles right and left Set up load sensing valves, Width extension locking, Axles Lifting Settings

TYRES : 12 Pcs Tyres 235/70R17,5" or 245/65R17,5 (J) 12 Pcs 17,5" Rims

ACCESSORIES & OPTIONS : 8 x Red+White Expanding to Sides Heavy Loading Reflectors: Front and Back side red+White At the front of lowbed, back side of red+White reflector , At back side of plate there will be 2 electrical sockets and lamp brackets to use turning lamps, 2 x Long vehicle warning plates with LED lamps, 10 Tonnes chain lashing rings, 2 pcs of warning turning lamps, SKF Automatic Greasing Unit

ELECTRICAL SYSTEM : Dasteri brand electrical system suitable for EU regulation, 24 V, ABS jack, 2 pcs 7 function stop lamp, 2 pcs plate lamp, Side lamps, Reflectors,

PAINT and COLOR

First Step : Sand Blasting all surface

First Layer : Barrier™ 80 (%80 Zinc-Reach) Coating Double Times - C5 (ISO 12944-2)


Second Layer : Epoxy Coating

Third Layer : Brand Premium Acrylic Paint

Fourth Layer : 2K Super Clear Coating for Protection and Shine (95-110 GU) 60 Degree Color of the trailer will be RAL

On platform anti slip painting

DETAIL PICTURES




sales@stutrailer.com

www.stutrailer.com

4 AXLE LOW LOADER



TECHNICAL DRAWING



SPECIFICATIONS

CHASSIS : Completely S700MC + S690QL strength steel welded with robotic arc welding machine high tension production

King pin load technical : 24.000 kg For Truck > 4x2 - 6x2 - 6x4

AXLES : 4 x 12 Tonnes Trax Brand Axles, All Axles are automatic hydraulic steering High Capacity air suspension balloons, 2 x 24 brake chamber, 4 x 24/30 emergency brake chambers 4 x automatic slack adjuster, Hydraulic Steering System manually and with remote control system

BRAKE : Drum brake System, Emergency Brake System, Loading Settings valve, Wabco 4S-3M EBS

REMOTE CONTROL FUNCTIONS : Remote control for hydraulic steering and set up gooseneck lifting, Set up platform lifting, Turns to axles right and left Set up load sensing valves, Width extension locking, Axles Lifting Settings

TYRES : 16 Pcs Tyres 235 /70R17,5" or 245/65R17,5 (J) 16 Pcs 17,5" Rims

ACCESSORIES & OPTIONS : 8 x Red+White Expanding to Sides Heavy Loading Reflectors: Front and Back side red+White At the front of lowbed, back side of red+White reflector , At back side of plate there will be 2 electrical sockets and lamp brackets to use turning lamps, 2 x Long vehicle warning plates with LED lamps, 10 Tonnes chain lashing rings, 2 pcs of warning turning lamps, SKF Automatic Greasing Unit

ELECTRICAL SYSTEM : Dasteri brand electrical system suitable for EU regulation, 24 V, ABS jack, 2 pcs 7 function stop lamp, 2 pcs plate lamp, Side lamps, Reflectors,

PAINT and COLOR

First Step : Sand Blasting all surface

First Layer : Barrier™ 80 (%80 Zinc-Reach) Coating Double Times - C5 (ISO 12944-2)


Second Layer : Epoxy Coating

Third Layer : Brand Premium Acrylic Paint

Fourth Layer : 2K Super Clear Coating for Protection and Shine (95-110 GU) 60 Degree Color of the trailer will be RAL

On platform anti slip painting

DETAIL PICTURES




sales@stutrailer.com

www.stutrailer.com

5 AXLE LOW LOADER



TECHNICAL DRAWING



SPECIFICATIONS

CHASSIS : Completely S700MC + S690QL strength steel welded with robotic arc welding machine high tension production

King pin load technical : 24.000 kg For Truck > 4x2 - 6x2 - 6x4

AXLES : 5 x 12 Tonnes Trax Brand Axles, All Axles are automatic hydraulic steering High Capacity air suspension balloons Hydraulic Steering System manually and with remote control system

BRAKE : Drum brake System, Emergency Brake System, Loading Settings valve, Wabco 4S-3M EBS

REMOTE CONTROL FUNCTIONS : Remote control for hydraulic steering and set up gooseneck lifting, Set up platform lifting, Turns to axles right and left Set up load sensing valves, Width extension locking, Axles Lifting Settings Without remote control driver may manage on PLC Screen on front of gooseneck

TYRES : 20 Pcs Tyres 235 /70R17,5" or 245/65R17,5 (J) 20 Pcs 17,5" Rims

ACCESSORIES & OPTIONS : 8 x Red+White Expanding to Sides Heavy Loading Reflectors: Front and Back side red+White At the front of lowbed, back side of red+White reflector , At back side of plate there will be 2 electrical sockets and lamp brackets to use turning lamps, 2 x Long vehicle warning plates with LED lamps, 10 Tonnes chain lashing rings, 2 pcs of warning turning lamps, SKF Automatic Greasing Unit

ELECTRICAL SYSTEM : Dasteri brand electrical system suitable for EU regulation, 24 V, ABS jack, 2 pcs 7 function stop lamp, 2 pcs plate lamp, Side lamps, Reflectors,

PAINT and COLOR

First Step : Sand Blasting all surface

First Layer : Barrier™ 80 (%80 Zinc-Reach) Coating Double Times - C5 (ISO 12944-2)

Second Layer : Epoxy Coating

Third Layer : Brand Premium Acrylic Paint

Fourth Layer : 2K Super Clear Coating for Protection and Shine (95-110 GU) 60 Degree Color of the trailer will be RAL

On platform anti slip painting

DETAIL PICTURES

